

星锐 钻石空气幕



“优化通风系统、弧线超薄型设计
- 造就全新大力神三代完美机型”

Optimization ventilation systems,
Ultra-thin arc design
Created Super thin series 3G
of perfect new models



Tap switch
轻触式按钮

It can be operated either by remote control or the touch of a button. It has high and low speed switch functions.

采用全新轻触式按键开关及红外遥控，且有高低两档调速功能。



Fan wheel
风轮

The unique fireplace flows the wind wheel air flow design. Can the high speed transient equilibrium low noise revolution.

独特贯流风轮风道设计：能高速动平衡低噪音运转。



Motor
电机

It adopts the technology of German electrical machinery, and runs safely for 5,000 consecutive hours.

引进德国电机技术，性能可靠，持续运行5000小时无故障。



Remote control
红外遥控

Remotely controlled and easy to operate. With the surge protection and power backup, it is even safer to use.

红外线遥控，操作轻松自如，且有断电自动启动功能，使用更安全。

特点 Characteristic:

Invisible Door

Making life more comfortable inside

Fuselage cover novel arc geometric design, succinct artistic. Uses the static electricity dusting pure metal outer cover the craft is advanced, does not distort does not rust. Adopting optimized electrical machinery, it operates reliably, and runs safely for 5,000 consecutive hours.

With a uniquely designed wind flow baffle, it can produce wind in all directions, working well in various environments.

机身外壳新颖弧线形设计，简洁美观。

采用静电喷粉全金属外壳，工艺先进，不变形不生锈。

采用优化空调电机，性能可靠，持续运行5000小时无故障。

独立导风板设计，风向可随意调节，并适用各种使用环境。



大力神三代超薄圆弧新技术参数:

型号 Model	尺寸 Dimension mm	额定频率 Frequency Hz	额定电压 Voltage VAC	输入功率(W) Max Input Power W	风量(m³/h) Air Volume m³/h	风速(m/s) Air Velocity m/s	噪音 Noise dB(A)	叶轮直径 Diameter of Wheel mm	重量 Net weight kg
FM-12048T, FM-12048Y	600x208x191	50	220-240	120	115	950 700	12 10	<55	120 9
FM-12095T, FM-12095Y	900x208x191	50	220-240	160	155	1255 950	12 10	<57	120 11
FM-12105T, FM-12105Y	1000x208x191	50	220-240	180	175	1380 1050	12 10	<58	120 12
FM-12125T, FM-12125Y	1200x208x191	50	220-240	200	195	1900 1250	12 10	<58	120 13
FM-12155T, FM-12155Y	1500x208x191	50	220-240	230	225	2350 1600	12 10	<59	120 15
FM-12185T, FM-12185Y	1800x208x191	50	220-240	330	300	2530 1720	12 10	<60	120 21
FM-12205T, FM-12205Y	2014x208x191	50	220-240	400	370	2650 1900	12 10	<61	120 24
FM-15095T, FM-15095Y	900x260x218	50	220-240	230	225	1680 1320	13 10	<69	150 13
FM-15125T, FM-15125Y	1200x260x218	50	220-240	300	295	2570 1800	13 10	<71	150 15
FM-15155T, FM-15155Y	1500x260x218	50	220-240	330	325	3210 2250	13 10	<71	150 18



Invisible Door Making life more comfortable inside



New design new numerical control alveolate grid, by super slim entire casing, made from galvanised steel. The entire machine has an arched geometric design, it can easy to installation and clean, save space. With a uniquely designed wind flow baffle, it can produces wind in all directions, working well in various environments. It can be operated either by remote control or at the touch of a button. It has high and low speed switch functions.

新颖数控蜂窝状面板，全金属超薄防锈外壳；
整机弧线形人性化设计，节约空间，安装方便，易清洁维护；
独特导风板设计，风向可自由调节；
采用遥控或按键式开关，有高、低两级调速功能。



星锐 ▶ 钻石 空气幕



Tap switch ▶ 轻触式按键



It can be operated either by remote control or the touch of a button, it has high and low speed switch functions.

采用全新轻触式按键开关及红外遥控，且有高低两级调速功能。

Fan wheel ▶ 动平衡风轮



The unique fireplace flows the wind wheel air flow design. Can the high speed transient equilibrium low noise revolution.独特的贯流风轮风道设计；能高速运动平衡低噪音运转。

Motor ▶ 高品质电机



It adopts the technology of German electrical machinery, and runs safely for 5,000 consecutive hours.

引进德国电机技术，性能可靠，持续运行5000小时无故障。

Remote control ▶ 红外线遥控



Remotely controlled and easy to operate. With the surge protection and power backup, it is even safer to use.

红外线遥控，操作轻松自如，且有断电自动保护功能，使用更安全。



大力神三代超薄风幕机技术参数:

▶ Super thin series 3G of perfect new models tech specs:

型号 Model	尺寸 Dimension	额定频率 Frequency	额定电压 Voltage	输入功率W Input power	风量(m³/h) Air volume	风速(m/s) Air velocity	噪音 Noise	叶轮直径 Diameter of Wheel	重量 Net weight
FM-1205A3, FM-1205A3Y	600x208x191	50	220-240	120	115 950 700	12 10 <55	120	9	
FM-1205A3, FM-1205A3Y	900x208x191	50	220-240	160	155 1255 950	12 10 <57	120	11	
FM-1210S3, FM-1210S3Y	1000x208x191	50	220-240	180	175 1380 1050	12 10 <58	120	12	
FM-1212S3, FM-1212S3Y	1200x208x191	50	220-240	200	195 1900 1250	12 10 <58	120	13	
FM-1215M3, FM-1215M3Y	1500x208x191	50	220-240	230	225 2350 1600	12 10 <59	120	15	
FM-1218S3, FM-1218S3Y	1800x208x191	50	220-240	330	300 2530 1720	12 10 <60	120	21	
FM-1220S3, FM-1220S3Y	2014x208x191	50	220-240	400	370 2650 1900	12 10 <61	120	24	
FM-1505A3, FM-1505A3Y	900x260x218	50	220-240	230	225 1680 1320	13 10 <59	150	13	
FM-1512M3, FM-1512M3Y	1200x260x218	50	220-240	300	295 2570 1800	13 10 <71	150	15	
FM-1515M3, FM-1515M3Y	1500x260x218	50	220-240	330	325 3210 2250	13 10 <71	150	18	

创造舒适的室内环境

